



DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) N° 305/2011

Pronova Glass-clear Silicone

N° 1900-25-431-02

1. Unique identification code of the product-type:

EN 15651-1: F-EXT-INT-CC

EN 15651-2: G-CC

EN15651-3: S

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see product packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer.

Joint sealant for facade elements for indoor and outdoor use

Joint sealant for glazing

Joint sealant for sanitary joints

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Pronova Dichtstoffe GmbH & Co. KG

Rudolf-Diesel-Straße 12

55543 Bad Kreuznach

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

System 3 for Reaction to Fire

7. In case of the declaration of performance concerning a construction product covered by harmonized standard:

The notified body SKZ-TeConA GmbH, number NB1213, has made the determination of the product type on the basis of type testing according to the system 3 and the class of fire behavior based on product verification after the system 3 issued.



8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance

Conditioning: Method A

Substrate: Glass without primer, aluminum with primer

Essential Characteristics	Declared performance	Harmonized standard
Reaction to fire	Class E	EN 15651-1:2012 EN 15651-2:2012 EN 15651-3:2012
Dangerous substances	Rated	
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10 %	
Tensile properties at maintained extension after immersion in water	No failure	
Adhesive/stress expansion action after the effects of heat, water and artificial light	No failure	
Resetting capacity	> 60 %	
Tensile properties	≤ 0,9 MPA	
Microorganisms, growth intensity DIN EN ISO 846	0 oder 1	
Durability	No failure	

10. The performance of the product identified in points 1 and 2 is conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Jörg Herberger
Managing director

Bad Kreuznach, 11.03.2021