



# DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) N° 305/2011

## Pronova Building Silicone

**N° 1900-39-100-01**

1. Unique identification code of the product-type:

**EN 15651-1: F-EXT-INT**

**EN 15651-2: G**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Batch number: see product packaging**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer.

**Sealant for facade for interior and exterior application**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Pronova Dichtstoffe GmbH & Co. KG**

**Rudolf-Diesel-Straße 12**

**55543 Bad Kreuznach**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**Not relevant**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3**

**System 3 for Reaction to Fire**

7. In case of the declaration of performance concerning a construction product covered by harmonized standard:

**The notified body SKZ-TeConA GmbH, identification number NB1213, has carried out the determination of the product type on the basis of a type test according to system 3 and issued the following: Test Report No. 105779/13-I**



8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Not relevant**

9. Declared performance

Conditioning: Method A

Substrate: Glass, aluminum

Essential Characteristics	Declared performance	Harmonized standard
Reaction to fire	Class E	EN 15651-1:2012 EN 15651-2:2012
Release of substances hazardous to the environment and health	NPD	
Resistance to flow	≤ 2 mm	
Loss of volume	≤ 20 %	
Tensile behavior (i.e. elongation behavior) at break (at 23°C)	No failure (60%)	
Tensile behavior (i.e. elongation behavior) at maintained extension after immersion in water	No failure (60%)	
Elasticity	> 70 %	
Durability	passed	

10. The performance of the product identified in points 1 and 2 is conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Jörg Herberger  
Managing director

Bad Kreuznach, 11.03.2021