

PRONOVA®

JOINT PRIMER

PROPERTIES AND TYPES OF APPLICATION:

PRONOVA Joint Primer is a solvent-free primer for strengthening porous, slightly sanding substrates in order to improve the adhesion of silicone and MS polymer sealants. Suitable for use with mineral materials such as plaster, masonry, sand-lime bricks, concrete, aerated concrete, gypsum plasterboard, fibre cement panels, bricks, facing bricks etc.

PRODUCT ADVANTAGES:

- ▶ Improves adhesion on all absorbent and porous substrates
- ▶ Solvent-free
- ▶ Excellent material compatibility
- ▶ Easy to apply
- ▶ Low odour



TECHNICAL INFORMATION:

Raw material base:

Fine-particle pure acrylic dispersion

Density:

Approx. 1.0 g/cm³

PREPARATION OF SUBSURFACE:

Substrates and bonding surfaces must be solid, clean and free of dust, oil and grease. Thoroughly remove all dirt, loose coatings, old sealant residues, loose mortar and rust.

APPLICATION:

Using a brush, cover the bonding surfaces with undiluted PRONOVA Joint Primer. Do not apply beyond the edges of the joint. After applying, leave the surfaces exposed to the air for approximately 20 to 30 minutes. In the case of very absorbent or sanding substrates, repeat the process.

STORAGE:

Store in cool, dry, frost-free conditions. Protect the container from continued direct sunlight! If stored properly in its unopened original container, PRONOVA Joint Primer has a shelf life of up to 36 months. Observe the shelf life date on the label.

DISPOSAL:

Only send completely empty packaging for recycling. Observe the local regulations when disposing of waste.

IMPORTANT INFORMATION:

When applying the product, wear suitable protective gloves and ensure adequate ventilation. Since there is a very large number of possible applications, carry out your own tests to ensure material compatibility, if in doubt.

Before applying the product, read the safety instructions on the container and the details in the safety data sheet. The safety data sheet can be found at www.pronova-dichtstoffe.de.

PACKAGING:

Package: 250-ml bottle

Packaging: 6 pieces/box

Colour: Colourless

The details provided in this technical information sheet are based on intensive application tests in the laboratory and in practice and are intended as guideline values and recommendations. The guideline values do not represent any guarantee or assurance. The responsibility for using the material in each case lies with the person using it. Since there are many different materials and the working conditions lie outside our sphere of influence, we recommend that you carry out your own tests, if in doubt.

Further information is available by telephone: 00 800 / 63333782 (free of charge for landline calls from Germany, Austria, Switzerland and The Netherlands).

The publication of this technical data sheet renders all previous editions of this data sheet void.

PRONOVA DICHTSTOFFE GMBH & CO. KG

Rudolf-Diesel-Strasse 12 • 55543 Bad Kreuznach • Germany
Telephone +49 671 920015-0 • Fax +49 671 920015 5020
info@pronova-dichtstoffe.de • www.pronova-dichtstoffe.de

PRONOVA[®]