

PRONOVA®

JOINT PERFECT

PROPERTIES AND TYPES OF APPLICATION:

PRONOVA Joint Perfect is a ready-to-use smoothing agent for smoothing silicone joints. Also suitable for MS polymers and polyurethane. Very good compatibility, also with paint systems and plastics (such as acrylic bathtubs). No discolouration or washing out of freshly applied joints. Solvent-free und biodegradable.

PRODUCT ADVANTAGES:

- ▶ Ready for use - quick & easy
- ▶ Improves the appearance of the joint
- ▶ Solvent-free
- ▶ Excellent material compatibility
- ▶ Does not attack the sealant
- ▶ Biodegradable



TECHNICAL INFORMATION:

Raw material base:	Tenside solution
Density:	Approx. 1.0 g/cm ³

APPLICATION:

Always use PRONOVA Joint Perfect undiluted and before a skin starts to form on the sealant. Spray sparingly onto the moist sealant and use a suitable smoothing tool (e.g. PRONOVA Joint Champion) to quickly smooth the sealant. Use clear water to remove any excess smoothing agent before it starts to dry. For a perfect appearance, we recommend masking the adjoining surfaces along the edges of the joint with adhesive tape. Remove the tape immediately after smoothing the joint.

STORAGE:

Store in cool, dry, frost-free conditions. Protect the container from continued direct sunlight! If stored properly in its unopened original container, PRONOVA Joint Perfect has a shelf life of up to 36 months. Observe the shelf life date on the label.

DISPOSAL:

Only send completely empty packaging for recycling. Observe the local regulations when disposing of waste.

IMPORTANT INFORMATION:

In the case of horizontal joints, prevent smoothing agent residues from accumulating in depressions in the sealant. Proceed with caution when jointing marble or natural stone tiles, since the smoothing agent can seep into these materials through their pores, which may result in undesirable blotches.

Before applying the product, read the safety instructions on the container and the details in the safety data sheet. The safety data sheet can be found at www.pronova-dichtstoffe.de.

PACKAGING:

Package: 250-ml bottle

Packaging: 6 pieces/box

Colour: Colourless

The details provided in this technical information sheet are based on intensive application tests in the laboratory and in practice and are intended as guideline values and recommendations. The guideline values do not represent any guarantee or assurance. The responsibility for using the material in each case lies with the person using it. Since there are many different materials and the working conditions lie outside our sphere of influence, we recommend that you carry out your own tests, if in doubt.

Further information is available by telephone: 00 800 / 63333782 (free of charge for landline calls from Germany, Austria, Switzerland and The Netherlands).

The publication of this technical data sheet renders all previous editions of this data sheet void.

PRONOVA DICHSTOFFE GMBH & CO. KG

Rudolf-Diesel-Strasse 12 • 55543 Bad Kreuznach • Germany
Telephone +49 671 920015-0 • Fax +49 671 920015 5020
info@pronova-dichtstoffe.de • www.pronova-dichtstoffe.de

PRONOVA[®]